

# HTTPIe: a CLI, cURL-like tool for humans

HTTPIe (pronounced *aitch-tee-tee-pie*) is a command line HTTP client. Its goal is to make CLI interaction with web services as human-friendly as possible. It provides a simple `http` command that allows for sending arbitrary HTTP requests using a simple and natural syntax, and displays colorized output. HTTPIe can be used for testing, debugging, and generally interacting with HTTP servers.

# Contents

<b>1</b>	<b>About this document</b>	<b>4</b>
<b>2</b>	<b>Main features</b>	<b>4</b>
<b>3</b>	<b>Installation</b>	<b>6</b>
3.1	macOS	6
3.2	Linux	6
3.3	Windows, etc.	6
3.4	Python version	6
3.5	Unstable version	6
<b>4</b>	<b>Usage</b>	<b>7</b>
4.1	Examples	7
<b>5</b>	<b>HTTP method</b>	<b>8</b>
<b>6</b>	<b>Request URL</b>	<b>8</b>
6.1	Querystring parameters	8
6.2	URL shortcuts for <code>localhost</code>	9
6.3	Other default schemes	9
6.4	<code>--path-as-is</code>	9
<b>7</b>	<b>Request items</b>	<b>10</b>
7.1	Escaping rules	10
<b>8</b>	<b>JSON</b>	<b>11</b>
8.1	Default behaviour	11
8.2	Explicit JSON	11
8.3	Non-string JSON fields	11
8.4	Raw and complex JSON	12
<b>9</b>	<b>Forms</b>	<b>12</b>
9.1	Regular forms	12
9.2	File upload forms	12
<b>10</b>	<b>HTTP headers</b>	<b>13</b>
10.1	Default request headers	13
10.2	Empty headers and header un-setting	13
10.3	Limiting response headers	14
<b>11</b>	<b>Offline mode</b>	<b>14</b>
<b>12</b>	<b>Cookies</b>	<b>14</b>
<b>13</b>	<b>Authentication</b>	<b>15</b>
13.1	Basic auth	15
13.2	Digest auth	15
13.3	Password prompt	15

13.4	Empty password	15
13.5	.netrc	15
13.6	Auth plugins	16
<b>14</b>	<b>HTTP redirects</b>	<b>16</b>
14.1	Follow Location	16
14.2	Showing intermediary redirect responses	16
14.3	Limiting maximum redirects followed	17
<b>15</b>	<b>Proxies</b>	<b>17</b>
15.1	Environment variables	17
15.2	SOCKS	17
<b>16</b>	<b>HTTPS</b>	<b>17</b>
16.1	Server SSL certificate verification	17
16.2	Custom CA bundle	17
16.3	Client side SSL certificate	18
16.4	SSL version	18
<b>17</b>	<b>Output options</b>	<b>18</b>
17.1	What parts of the HTTP exchange should be printed	19
17.2	Viewing intermediary requests/responses	19
17.3	Conditional body download	19
<b>18</b>	<b>Redirected Input</b>	<b>20</b>
18.1	Request data from a filename	21
<b>19</b>	<b>Terminal output</b>	<b>21</b>
19.1	Colors and formatting	21
19.2	Binary data	21
<b>20</b>	<b>Redirected output</b>	<b>22</b>
<b>21</b>	<b>Download mode</b>	<b>22</b>
21.1	Downloaded filename	23
21.2	Piping while downloading	23
21.3	Resuming downloads	23
21.4	Other notes	23
<b>22</b>	<b>Streamed responses</b>	<b>23</b>
22.1	Disabling buffering	24
22.2	Examples use cases	24
<b>23</b>	<b>Sessions</b>	<b>24</b>
23.1	Named sessions	24
23.2	Anonymous sessions	25
23.3	Readonly session	25
<b>24</b>	<b>Config</b>	<b>25</b>

24.1	Config file directory	25
24.2	Configurable options	26
24.2.1	default_options	26
24.3	Un-setting previously specified options	26
<b>25</b>	<b>Scripting</b>	<b>26</b>
25.1	Best practices	27
<b>26</b>	<b>Meta</b>	<b>27</b>
26.1	Interface design	27
26.2	User support	27
26.3	Related projects	28
26.3.1	Dependencies	28
26.3.2	HTTPie friends	28
26.3.3	Alternatives	28
26.4	Contributing	28
26.5	Change log	28
26.6	Artwork	28
26.7	Licence	28
26.8	Authors	28

# 1 About this document

This documentation is best viewed at <httpie.org/docs>, where you can select your corresponding HTTPie version as well as run examples directly from the browser using a [termible.io](http://termible.io) embedded terminal. If you are reading this on GitHub, then this text covers the current *development* version. You are invited to submit fixes and improvements to the docs by editing [README.rst](#).

# 2 Main features

- Expressive and intuitive syntax
- Formatted and colorized terminal output
- Built-in JSON support
- Forms and file uploads
- HTTPS, proxies, and authentication
- Arbitrary request data
- Custom headers
- Persistent sessions
- Wget-like downloads
- Linux, macOS and Windows support
- Plugins
- Documentation
- Test coverage

```
bash
$ curl -i -X PUT httpbin.org/put -H Content-Type:application/json -d '{"hello": "world"}'
HTTP/1.1 200 OK
Connection: keep-alive
Server: gunicorn/19.9.0
Date: Fri, 02 Nov 2018 16:53:05 GMT
Content-Type: application/json
Content-Length: 452
Access-Control-Allow-Credentials: true
Access-Control-Allow-Origin: *
```

```
bash
$ http PUT httpbin.org/put hello=world
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Origin: *
Connection: keep-alive
Content-Length: 452
Content-Type: application/json
Date: Fri, 02 Nov 2018 16:53:05 GMT
Server: gunicorn/19.9.0
Via: 1.1 vegur

{
  "args": {},
  "data": "{\\\"hello\\\": \\\"world\\\"}",
  "files": {},
  "form": {},
  "headers": {
    "Accept": "application/json, */*",
    "Accept-Encoding": "gzip, deflate",
    "Connection": "close",
    "Content-Length": "18",
    "Content-Type": "application/json",
    "Host": "httpbin.org",
    "User-Agent": "HTTPie/1.0.0"
  },
  "json": {
    "hello": "world"
  },
  "origin": "89.102.136.126",
  "url": "http://httpbin.org/put"
}
```

## 3 Installation

### 3.1 macOS

On macOS, HTTPie can be installed via [Homebrew](#) (recommended):

```
$ brew install httpie
```

A MacPorts *port* is also available:

```
$ port install httpie
```

### 3.2 Linux

Most Linux distributions provide a package that can be installed using the system package manager, for example:

```
# Debian, Ubuntu, etc.  
$ apt install httpie
```

```
# Fedora  
$ dnf install httpie
```

```
# CentOS, RHEL, ...  
$ yum install httpie
```

```
# Arch Linux  
$ pacman -S httpie
```

### 3.3 Windows, etc.

A universal installation method (that works on Windows, Mac OS X, Linux, ..., and always provides the latest version) is to use [pip](#):

```
# Make sure we have an up-to-date version of pip and setuptools:  
$ pip install --upgrade pip setuptools  
  
$ pip install --upgrade httpie
```

(If `pip` installation fails for some reason, you can try `easy_install httpie` as a fallback.)

### 3.4 Python version

Python version 3.6 or greater is required.

### 3.5 Unstable version

You can also install the latest unreleased development version directly from the `master` branch on GitHub. It is a work-in-progress of a future stable release so the experience might be not as smooth.

On macOS you can install it with Homebrew:

```
$ brew install httpie --HEAD
```

Otherwise with pip:

```
$ pip install --upgrade https://github.com/jakubroztocil/httpie/archive/master.tar.gz
```

Verify that now we have the [current development version identifier](#) with the `-dev` suffix, for example:

```
$ http --version  
# 2.0.0-dev
```

## 4 Usage

Hello World:

```
$ http https://httpie.org/hello
```

Synopsis:

```
$ http [flags] [METHOD] URL [ITEM [ITEM]]
```

See also `http --help`.

### 4.1 Examples

Custom [HTTP method](#), [HTTP headers](#) and [JSON data](#):

```
$ http PUT httpbin.org/put X-API-Token:123 name=John
```

Submitting [forms](#):

```
$ http -f POST httpbin.org/post hello=World
```

See the request that is being sent using one of the [output options](#):

```
$ http -v httpbin.org/get
```

Build and print a request without sending it using [offline mode](#):

```
$ http --offline httpbin.org/post hello=offline
```

Use [Github API](#) to post a comment on an [issue](#) with [authentication](#):

```
$ http -a USERNAME POST https://api.github.com/repos/jakubroztocil/httpie/issues/83/comments body='HTTPIe is awesome! :heart:'
```

Upload a file using [redirected input](#):

```
$ http httpbin.org/post < files/data.json
```

Download a file and save it via [redirected output](#):

```
$ http httpbin.org/image/png > image.png
```

Download a file `wget` style:

```
$ http --download httpbin.org/image/png
```

Use named [sessions](#) to make certain aspects of the communication persistent between requests to the same host:

```
$ http --session=logged-in -a username:password httpbin.org/get API-Key:123
```

```
$ http --session=logged-in httpbin.org/headers
```

Set a custom `Host` header to work around missing DNS records:

```
$ http localhost:8000 Host:example.com
```

## 5 HTTP method

The name of the HTTP method comes right before the URL argument:

```
$ http DELETE httpbin.org/delete
```

Which looks similar to the actual `Request-Line` that is sent:

```
DELETE /delete HTTP/1.1
```

When the `METHOD` argument is omitted from the command, HTTPie defaults to either `GET` (with no request data) or `POST` (with request data).

## 6 Request URL

The only information HTTPie needs to perform a request is a URL. The default scheme is, somewhat unsurprisingly, `http://`, and can be omitted from the argument – `http example.org` works just fine.

### 6.1 Querystring parameters

If you find yourself manually constructing URLs with querystring parameters on the terminal, you may appreciate the `param==value` syntax for appending URL parameters.

With that, you don't have to worry about escaping the `&` separators for your shell. Additionally, any special characters in the parameter name or value get automatically URL-escaped (as opposed to parameters specified in the full URL, which HTTPie doesn't modify).

```
$ http https://api.github.com/search/repositories q==httpie per_page==1
```

```
GET /search/repositories?q=httpie&per_page=1 HTTP/1.1
```



## 6.2 URL shortcuts for localhost

Additionally, curl-like shorthand for localhost is supported. This means that, for example `:3000` would expand to `http://localhost:3000`. If the port is omitted, then port 80 is assumed.

```
$ http :/foo
```

```
GET /foo HTTP/1.1
Host: localhost
```

```
$ http :3000/bar
```

```
GET /bar HTTP/1.1
Host: localhost:3000
```

```
$ http :
```

```
GET / HTTP/1.1
Host: localhost
```

## 6.3 Other default schemes

When HTTPie is invoked as `https` then the default scheme is `https://` (`$ https example.org` will make a request to `https://example.org`).

You can also use the `--default-scheme <URL_SCHEME>` option to create shortcuts for other protocols than HTTP (possibly supported via plugins). Example for the [httpie-unixsocket](#) plugin:

```
# Before
$ http http+unix://%2Fvar%2Frun%2Fdocker.sock/info
```

```
# Create an alias
$ alias http-unix='http --default-scheme="http+unix" '
```

```
# Now the scheme can be omitted
$ http-unix %2Fvar%2Frun%2Fdocker.sock/info
```

## 6.4 --path-as-is

The standard behaviour of HTTP clients is to normalize the path portion of URLs by squashing dot segments as a typically filesystem would:

```
$ http -v example.org/../../etc/password
```

```
GET /etc/password HTTP/1.1
```

The `--path-as-is` option allows you to disable this behavior:

```
$ http --path-as-is -v example.org/../../../../etc/password
```

```
GET ../../etc/password HTTP/1.1
```

## 7 Request items

There are a few different *request item* types that provide a convenient mechanism for specifying HTTP headers, simple JSON and form data, files, and URL parameters.

They are key/value pairs specified after the URL. All have in common that they become part of the actual request that is sent and that their type is distinguished only by the separator used: `:`, `=`, `:=`, `==`, `@`, `=@`, and `:=@`. The ones with an `@` expect a file path as value.

Item Type	Description
HTTP Headers <code>Name:Value</code>	Arbitrary HTTP header, e.g. <code>X-API-Token:123</code> .
URL parameters <code>name==value</code>	Appends the given name/value pair as a query string parameter to the URL. The <code>==</code> separator is used.
Data Fields <code>field=value</code> , <code>field=@file.txt</code>	Request data fields to be serialized as a JSON object (default), or to be form-encoded ( <code>--form</code> , <code>-f</code> ).
Raw JSON fields <code>field:=json</code> , <code>field:=@file.json</code>	Useful when sending JSON and one or more fields need to be a Boolean, Number, nested Object, or an Array, e.g., <code>meals:='["ham","spam"]'</code> or <code>pies:=[1,2,3]</code> (note the quotes).
Form File Fields <code>field@/dir/file</code>	Only available with <code>--form</code> , <code>-f</code> . For example <code>screenshot@~/Pictures/img.png</code> . The presence of a file field results in a <code>multipart/form-data</code> request.

Note that data fields aren't the only way to specify request data: [Redirected input](#) is a mechanism for passing arbitrary request data.

### 7.1 Escaping rules

You can use `\` to escape characters that shouldn't be used as separators (or parts thereof). For instance, `foo\==bar` will become a data key/value pair (`foo=` and `bar`) instead of a URL parameter.

Often it is necessary to quote the values, e.g. `foo='bar baz'`.

If any of the field names or headers starts with a minus (e.g., `-fieldname`), you need to place all such items after the special token `--` to prevent confusion with `--arguments`:

```
$ http httpbin.org/post -- -name-starting-with-dash=foo -Unusual-Header:bar
```

```
POST /post HTTP/1.1
-Unusual-Header: bar
Content-Type: application/json

{
  "-name-starting-with-dash": "foo"
}
```

## 8 JSON

JSON is the *lingua franca* of modern web services and it is also the **implicit content type** HTTPie uses by default.

Simple example:

```
$ http PUT httpbin.org/put name=John email=john@example.org
```

```
PUT / HTTP/1.1
Accept: application/json, */*;q=0.5
Accept-Encoding: gzip, deflate
Content-Type: application/json
Host: httpbin.org

{
  "name": "John",
  "email": "john@example.org"
}
```

### 8.1 Default behaviour

If your command includes some data [request items](#), they are serialized as a JSON object by default. HTTPie also automatically sets the following headers, both of which can be overwritten:

Content-Type	application/json
Accept	application/json, */*;q=0.5

### 8.2 Explicit JSON

You can use `--json`, `-j` to explicitly set `Accept` to `application/json` regardless of whether you are sending data (it's a shortcut for setting the header via the usual header notation: `http url Accept:'application/json, */*;q=0.5'`). Additionally, HTTPie will try to detect JSON responses even when the `Content-Type` is incorrectly `text/plain` or `unknown`.

### 8.3 Non-string JSON fields

Non-string JSON fields use the `:=` separator, which allows you to embed arbitrary JSON data into the resulting JSON object. Additionally, text and raw JSON files can also be embedded into fields using `=@` and `:=@`:

```
$ http PUT httpbin.org/put \
  name=John \                               # String (default)
  age:=29 \                                  # Raw JSON - Number
  married:=false \                           # Raw JSON - Boolean
  hobbies:='["http", "pies"]' \             # Raw JSON - Array
  favorite:='{ "tool": "HTTPie" }' \         # Raw JSON - Object
  bookmarks:=@files/data.json \             # Embed JSON file
  description=@files/text.txt               # Embed text file
```

```
PUT /person/1 HTTP/1.1
Accept: application/json, */*;q=0.5
Content-Type: application/json
Host: httpbin.org
```

```
{
  "age": 29,
  "hobbies": [
    "http",
    "pies"
  ],
  "description": "John is a nice guy who likes pies.",
  "married": false,
  "name": "John",
  "favorite": {
    "tool": "HTTPIe"
  },
  "bookmarks": {
    "HTTPIe": "https://httpie.org",
  }
}
```

## 8.4 Raw and complex JSON

Please note that with the [request items](#) data field syntax, commands can quickly become unwieldy when sending complex structures. In such cases, it's better to pass the full raw JSON data via [redirected input](#), for example:

```
$ echo '{"hello": "world"}' | http POST httpbin.org/post
```

```
$ http POST httpbin.org/post < files/data.json
```

Furthermore, this syntax only allows you to send an object as the JSON document, but not an array, etc. Here, again, the solution is to use [redirected input](#).

## 9 Forms

Submitting forms is very similar to sending [JSON](#) requests. Often the only difference is in adding the `--form`, `-f` option, which ensures that data fields are serialized as, and `Content-Type` is set to, `application/x-www-form-urlencoded; charset=utf-8`. It is possible to make form data the implicit content type instead of JSON via the [config](#) file.

### 9.1 Regular forms

```
$ http --form POST httpbin.org/post name='John Smith'
```

```
POST /post HTTP/1.1
Content-Type: application/x-www-form-urlencoded; charset=utf-8

name=John+Smith
```

### 9.2 File upload forms

If one or more file fields is present, the serialization and content type is `multipart/form-data`:

```
$ http -f POST httpbin.org/post name='John Smith' cv@~/files/data.xml
```

The request above is the same as if the following HTML form were submitted:

```
<form enctype="multipart/form-data" method="post" action="http://example.com/jobs">
  <input type="text" name="name" />
  <input type="file" name="cv" />
</form>
```

Note that @ is used to simulate a file upload form field, whereas =@ just embeds the file content as a regular text field value.

## 10 HTTP headers

To set custom headers you can use the Header:Value notation:

```
$ http httpbin.org/headers User-Agent:Bacon/1.0 'Cookie:valued-visitor=yes;foo=bar' \
  X-Foo:Bar Referer:https://httpie.org/
```

```
GET /headers HTTP/1.1
Accept: */*
Accept-Encoding: gzip, deflate
Cookie: valued-visitor=yes;foo=bar
Host: httpbin.org
Referer: https://httpie.org/
User-Agent: Bacon/1.0
X-Foo: Bar
```

### 10.1 Default request headers

There are a couple of default headers that HTTPie sets:

```
GET / HTTP/1.1
Accept: */*
Accept-Encoding: gzip, deflate
User-Agent: HTTPie/<version>
Host: <taken-from-URL>
```

Any of these except Host can be overwritten and some of them unset.

### 10.2 Empty headers and header un-setting

To unset a previously specified header (such a one of the default headers), use Header::

```
$ http httpbin.org/headers Accept: User-Agent:
```

To send a header with an empty value, use Header;:

```
$ http httpbin.org/headers 'Header;'
```

## 10.3 Limiting response headers

The `--max-headers=n` options allows you to control the number of headers HTTPie reads before giving up (the default 0, i.e., there's no limit).

```
$ http --max-headers=100 httpbin.org/get
```

## 11 Offline mode

Use `--offline` to construct HTTP requests without sending them anywhere. With `--offline`, HTTPie builds a request based on the specified options and arguments, prints it to `stdout`, and then exists. It works completely offline; no network connection is ever made. This has a number of use cases, including:

Generating API documentation examples that you can copy & paste without sending a request:

```
$ http --offline POST server.chess/api/games API-Key:ZZZ w=magnus b=hikaru t=180 i=2
```

```
$ http --offline MOVE server.chess/api/games/123 API-Key:ZZZ p=b a=R1a3 t=77
```

Generating raw requests that can be sent with any other client:

```
# 1. save a raw request to a file:
$ http --offline POST httpbin.org/post hello=world > request.http
```

```
# 2. send it over the wire with, for example, the fantastic netcat tool:
$ nc httpbin.org 80 < request.http
```

You can also use the `--offline` mode for debugging and exploring HTTP and HTTPie, and for “dry runs”.

`--offline` has the side-effect of automatically activating `--print=HB`, i.e., both the request headers and the body are printed. You can customize the output with the usual [output options](#), with the exception that there is not response to be printed. You can use `--offline` in combination with all the other options (e.g., `--session`).

## 12 Cookies

HTTP clients send cookies to the server as regular [HTTP headers](#). That means, HTTPie does not offer any special syntax for specifying cookies — the usual `Header:Value` notation is used:

Send a single cookie:

```
$ http httpbin.org/cookies Cookie:sessionid=foo
```

```
GET / HTTP/1.1
Accept: */*
Accept-Encoding: gzip, deflate
Connection: keep-alive
Cookie: sessionid=foo
Host: httpbin.org
User-Agent: HTTPie/0.9.9
```

Send multiple cookies (note the header is quoted to prevent the shell from interpreting the `;`):

```
$ http httpbin.org/cookies 'Cookie:sessionid=foo;another-cookie=bar'
```

```
GET / HTTP/1.1
Accept: */*
Accept-Encoding: gzip, deflate
Connection: keep-alive
Cookie: sessionid=foo;another-cookie=bar
Host: httpbin.org
User-Agent: HTTPie/0.9.9
```

If you often deal with cookies in your requests, then chances are you'd appreciate the [sessions](#) feature.

## 13 Authentication

The currently supported authentication schemes are Basic and Digest (see [auth plugins](#) for more). There are two flags that control authentication:

<code>--auth, -a</code>	Pass a <code>username:password</code> pair as the argument. Or, if you only specify a username ( <code>-a username</code> ), you'll be prompted for the password before the request is sent. To send an empty password, pass <code>username:.</code> The <code>username:password@hostname</code> URL syntax is supported as well (but credentials passed via <code>-a</code> have higher priority).
<code>--auth-type, -A</code>	Specify the auth mechanism. Possible values are <code>basic</code> and <code>digest</code> . The default value is <code>basic</code> so it can often be omitted.

### 13.1 Basic auth

```
$ http -a username:password httpbin.org/basic-auth/username/password
```

### 13.2 Digest auth

```
$ http -A digest -a username:password httpbin.org/digest-auth/httpie/username/password
```

### 13.3 Password prompt

```
$ http -a username httpbin.org/basic-auth/username/password
```

### 13.4 Empty password

```
$ http -a username: httpbin.org/headers
```

### 13.5 .netrc

Authentication information from your `~/ .netrc` file is by default honored as well.

For example:

```
$ cat ~/.netrc
machine httpbin.org
```

```
login httpie
password test
```

```
$ http httpbin.org/basic-auth/httpie/test
HTTP/1.1 200 OK
[...]
```

This can be disabled with the `--ignore-netrc` option:

```
$ http --ignore-netrc httpbin.org/basic-auth/httpie/test
HTTP/1.1 401 UNAUTHORIZED
[...]
```

## 13.6 Auth plugins

Additional authentication mechanism can be installed as plugins. They can be found on the [Python Package Index](#). Here's a few picks:

- [httpie-api-auth](#): ApiAuth
- [httpie-aws-auth](#): AWS / Amazon S3
- [httpie-edgegrid](#): EdgeGrid
- [httpie-hmac-auth](#): HMAC
- [httpie-jwt-auth](#): JWTAuth (JSON Web Tokens)
- [httpie-negotiate](#): SPNEGO (GSS Negotiate)
- [httpie-ntlm](#): NTLM (NT LAN Manager)
- [httpie-oauth](#): OAuth
- [requests-hawk](#): Hawk

## 14 HTTP redirects

By default, HTTP redirects are not followed and only the first response is shown:

```
$ http httpbin.org/redirect/3
```

### 14.1 Follow Location

To instruct HTTPie to follow the `Location` header of 30x responses and show the final response instead, use the `--follow`, `-F` option:

```
$ http --follow httpbin.org/redirect/3
```

### 14.2 Showing intermediary redirect responses

If you additionally wish to see the intermediary requests/responses, then use the `--all` option as well:

```
$ http --follow --all httpbin.org/redirect/3
```



## 14.3 Limiting maximum redirects followed

To change the default limit of maximum 30 redirects, use the `--max-redirects=<limit>` option:

```
$ http --follow --all --max-redirects=2 httpbin.org/redirect/3
```

## 15 Proxies

You can specify proxies to be used through the `--proxy` argument for each protocol (which is included in the value in case of redirects across protocols):

```
$ http --proxy=http:http://10.10.1.10:3128 --proxy=https:https://10.10.1.10:1080 example.org
```

With Basic authentication:

```
$ http --proxy=http:http://user:pass@10.10.1.10:3128 example.org
```

### 15.1 Environment variables

You can also configure proxies by environment variables `ALL_PROXY`, `HTTP_PROXY` and `HTTPS_PROXY`, and the underlying Requests library will pick them up as well. If you want to disable proxies configured through the environment variables for certain hosts, you can specify them in `NO_PROXY`.

In your `~/.bash_profile`:

```
export HTTP_PROXY=http://10.10.1.10:3128
export HTTPS_PROXY=https://10.10.1.10:1080
export NO_PROXY=localhost,example.com
```

### 15.2 SOCKS

Homebrew-installed HTTPie comes with SOCKS proxy support out of the box. To enable SOCKS proxy support for non-Homebrew installations, you'll might need to install `requests[socks]` manually using `pip`:

```
$ pip install -U requests[socks]
```

Usage is the same as for other types of [proxies](#):

```
$ http --proxy=http:socks5://user:pass@host:port --proxy=https:socks5://user:pass@host:port example.org
```

## 16 HTTPS

### 16.1 Server SSL certificate verification

To skip the host's SSL certificate verification, you can pass `--verify=no` (default is `yes`):

```
$ http --verify=no https://httpbin.org/get
```

### 16.2 Custom CA bundle

You can also use `--verify=<CA_BUNDLE_PATH>` to set a custom CA bundle path:

```
$ http --verify=/ssl/custom_ca_bundle https://example.org
```

## 16.3 Client side SSL certificate

To use a client side certificate for the SSL communication, you can pass the path of the cert file with `--cert`:

```
$ http --cert=client.pem https://example.org
```

If the private key is not contained in the cert file you may pass the path of the key file with `--cert-key`:

```
$ http --cert=client.crt --cert-key=client.key https://example.org
```

## 16.4 SSL version

Use the `--ssl=<PROTOCOL>` to specify the desired protocol version to use. This will default to SSL v2.3 which will negotiate the highest protocol that both the server and your installation of OpenSSL support. The available protocols are `ssl2.3`, `ssl3`, `tlsl`, `tlsl1`, `tlsl1.1`, `tlsl1.2`, `tlsl1.3`. (The actually available set of protocols may vary depending on your OpenSSL installation.)

```
# Specify the vulnerable SSL v3 protocol to talk to an outdated server:
$ http --ssl=ssl3 https://vulnerable.example.org
```

## 17 Output options

By default, HTTPie only outputs the final response and the whole response message is printed (headers as well as the body). You can control what should be printed via several options:

<code>--headers, -h</code>	Only the response headers are printed.
<code>--body, -b</code>	Only the response body is printed.
<code>--verbose, -v</code>	Print the whole HTTP exchange (request and response). This option also enables <code>--all</code> (see below).
<code>--print, -p</code>	Selects parts of the HTTP exchange.

`--verbose` can often be useful for debugging the request and generating documentation examples:

```
$ http --verbose PUT httpbin.org/put hello=world
PUT /put HTTP/1.1
Accept: application/json, */*;q=0.5
Accept-Encoding: gzip, deflate
Content-Type: application/json
Host: httpbin.org
User-Agent: HTTPie/0.2.7dev

{
  "hello": "world"
}

HTTP/1.1 200 OK
Connection: keep-alive
Content-Length: 477
```

```
Content-Type: application/json
Date: Sun, 05 Aug 2012 00:25:23 GMT
Server: unicorn/0.13.4
```

```
{
  [...]
}
```

## 17.1 What parts of the HTTP exchange should be printed

All the other [output options](#) are under the hood just shortcuts for the more powerful `--print`, `-p`. It accepts a string of characters each of which represents a specific part of the HTTP exchange:

Character	Stands for
H	request headers
B	request body
h	response headers
b	response body

Print request and response headers:

```
$ http --print=Hh PUT httpbin.org/put hello=world
```

## 17.2 Viewing intermediary requests/responses

To see all the HTTP communication, i.e. the final request/response as well as any possible intermediary requests/responses, use the `--all` option. The intermediary HTTP communication include followed redirects (with `--follow`), the first unauthorized request when HTTP digest authentication is used (`--auth=digest`), etc.

```
# Include all responses that lead to the final one:
$ http --all --follow httpbin.org/redirect/3
```

The intermediary requests/response are by default formatted according to `--print`, `-p` (and its shortcuts described above). If you'd like to change that, use the `--history-print`, `-P` option. It takes the same arguments as `--print`, `-p` but applies to the intermediary requests only.

```
# Print the intermediary requests/responses differently than the final one:
$ http -A digest -a foo:bar --all -p Hh -P H httpbin.org/digest-auth/auth/foo/bar
```

## 17.3 Conditional body download

As an optimization, the response body is downloaded from the server only if it's part of the output. This is similar to performing a `HEAD` request, except that it applies to any HTTP method you use.

Let's say that there is an API that returns the whole resource when it is updated, but you are only interested in the response headers to see the status code after an update:

```
$ http --headers PATCH httpbin.org/patch name='New Name'
```

Since we are only printing the HTTP headers here, the connection to the server is closed as soon as all the response headers have been received. Therefore, bandwidth and time isn't wasted downloading the

body which you don't care about. The response headers are downloaded always, even if they are not part of the output

## 18 Redirected Input

The universal method for passing request data is through redirected `stdin` (standard input)—piping. Such data is buffered and then with no further processing used as the request body. There are multiple useful ways to use piping:

Redirect from a file:

```
$ http PUT httpbin.org/put X-API-Token:123 < files/data.json
```

Or the output of another program:

```
$ grep '401 Unauthorized' /var/log/httpd/error_log | http POST httpbin.org/post
```

You can use `echo` for simple data:

```
$ echo '{"name": "John"}' | http PATCH httpbin.org/patch X-API-Token:123
```

You can also use a Bash *here string*:

```
$ http httpbin.org/post <<<'{"name": "John"}'
```

You can even pipe web services together using HTTPie:

```
$ http GET https://api.github.com/repos/jakubroztocil/httpie | http POST httpbin.org/post
```

You can use `cat` to enter multiline data on the terminal:

```
$ cat | http POST httpbin.org/post
<paste>
^D
```

```
$ cat | http POST httpbin.org/post Content-Type:text/plain
- buy milk
- call parents
^D
```

On OS X, you can send the contents of the clipboard with `pbpaste`:

```
$ pbpaste | http PUT httpbin.org/put
```

Passing data through `stdin` cannot be combined with data fields specified on the command line:

```
$ echo 'data' | http POST example.org more=data # This is invalid
```

To prevent HTTPie from reading `stdin` data you can use the `--ignore-stdin` option.

## 18.1 Request data from a filename

An alternative to redirected `stdin` is specifying a filename (as `@/path/to/file`) whose content is used as if it came from `stdin`.

It has the advantage that the `Content-Type` header is automatically set to the appropriate value based on the filename extension. For example, the following request sends the verbatim contents of that XML file with `Content-Type: application/xml`:

```
$ http PUT httpbin.org/put @files/data.xml
```

## 19 Terminal output

HTTPie does several things by default in order to make its terminal output easy to read.

### 19.1 Colors and formatting

Syntax highlighting is applied to HTTP headers and bodies (where it makes sense). You can choose your preferred color scheme via the `--style` option if you don't like the default one. There dozens of styles available, here are just a few special or notable ones:

auto	Follows your terminal ANSI color styles. This is the default style used by HTTPie.
default	Default styles of the underlying Pygments library. Not actually used by default by HTTPie. You can enable it with <code>--style=default</code>
monokai	A popular color scheme. Enable with <code>--style=monokai</code> .
fruity	A bold, colorful scheme. Enable with <code>--style=fruity</code> .
...	See <code>\$ http --help</code> for all the possible <code>--style</code> values.

Also, the following formatting is applied:

- HTTP headers are sorted by name.
- JSON data is indented, sorted by keys, and unicode escapes are converted to the characters they represent.

One of these options can be used to control output processing:

<code>--pretty=all</code>	Apply both colors and formatting. Default for terminal output.
<code>--pretty=colors</code>	Apply colors.
<code>--pretty=format</code>	Apply formatting.
<code>--pretty=none</code>	Disables output processing. Default for redirected output.

### 19.2 Binary data

Binary data is suppressed for terminal output, which makes it safe to perform requests to URLs that send back binary data. Binary data is suppressed also in redirected, but prettified output. The connection is closed as soon as we know that the response body is binary,

```
$ http httpbin.org/bytes/2000
```

You will nearly instantly see something like this:

```
HTTP/1.1 200 OK
Content-Type: application/octet-stream
```

```
+-----+
| NOTE: binary data not shown in terminal |
+-----+
```

## 20 Redirected output

HTTPie uses a different set of defaults for redirected output than for [terminal output](#). The differences being:

- Formatting and colors aren't applied (unless `--pretty` is specified).
- Only the response body is printed (unless one of the [output options](#) is set).
- Also, binary data isn't suppressed.

The reason is to make piping HTTPie's output to another programs and downloading files work with no extra flags. Most of the time, only the raw response body is of an interest when the output is redirected.

Download a file:

```
$ http httpbin.org/image/png > image.png
```

Download an image of Octocat, resize it using ImageMagick, upload it elsewhere:

```
$ http octodex.github.com/images/original.jpg | convert - -resize 25% - | http example.org/Octocats
```

Force colorizing and formatting, and show both the request and the response in `less` pager:

```
$ http --pretty=all --verbose httpbin.org/get | less -R
```

The `-R` flag tells `less` to interpret color escape sequences included HTTPie's output.

You can create a shortcut for invoking HTTPie with colorized and paged output by adding the following to your `~/.bash_profile`:

```
function httpless {
    # `httpless example.org'
    http --pretty=all --print=hb "$@" | less -R;
}
```

## 21 Download mode

HTTPie features a download mode in which it acts similarly to `wget`.

When enabled using the `--download`, `-d` flag, response headers are printed to the terminal (`stderr`), and a progress bar is shown while the response body is being saved to a file.

```
$ http --download https://github.com/jakubroztocil/httpie/archive/master.tar.gz
```

```
HTTP/1.1 200 OK
Content-Disposition: attachment; filename=httpie-master.tar.gz
Content-Length: 257336
Content-Type: application/x-gzip
```

```
Downloading 251.30 kB to "httpie-master.tar.gz"  
Done. 251.30 kB in 2.73862s (91.76 kB/s)
```

## 21.1 Downloaded filename

There are three mutually exclusive ways through which HTTPie determines the output filename (with decreasing priority):

1. You can explicitly provide it via `--output`, `-o`. The file gets overwritten if it already exists (or appended to with `--continue`, `-c`).
2. The server may specify the filename in the optional `Content-Disposition` response header. Any leading dots are stripped from a server-provided filename.
3. The last resort HTTPie uses is to generate the filename from a combination of the request URL and the response `Content-Type`. The initial URL is always used as the basis for the generated filename — even if there has been one or more redirects.

To prevent data loss by overwriting, HTTPie adds a unique numerical suffix to the filename when necessary (unless specified with `--output`, `-o`).

## 21.2 Piping while downloading

You can also redirect the response body to another program while the response headers and progress are still shown in the terminal:

```
$ http -d https://github.com/jakubroztocil/httpie/archive/master.tar.gz | tar xzf -
```

## 21.3 Resuming downloads

If `--output`, `-o` is specified, you can resume a partial download using the `--continue`, `-c` option. This only works with servers that support `Range` requests and `206 Partial Content` responses. If the server doesn't support that, the whole file will simply be downloaded:

```
$ http -dco file.zip example.org/file
```

## 21.4 Other notes

- The `--download` option only changes how the response body is treated.
- You can still set custom headers, use sessions, `--verbose`, `-v`, etc.
- `--download` always implies `--follow` (redirects are followed).
- `--download` also implies `--check-status` (error HTTP status will result in a non-zero exist static code).
- HTTPie exits with status code 1 (error) if the body hasn't been fully downloaded.
- `Accept-Encoding` cannot be set with `--download`.

## 22 Streamed responses

Responses are downloaded and printed in chunks which allows for streaming and large file downloads without using too much memory. However, when [colors and formatting](#) is applied, the whole response is buffered and only then processed at once.

## 22.1 Disabling buffering

You can use the `--stream`, `-S` flag to make two things happen:

1. The output is flushed in much smaller chunks without any buffering, which makes HTTPie behave kind of like `tail -f` for URLs.
2. Streaming becomes enabled even when the output is prettified: It will be applied to each line of the response and flushed immediately. This makes it possible to have a nice output for long-lived requests, such as one to the Twitter streaming API.

## 22.2 Examples use cases

Prettified streamed response:

```
$ http --stream -f -a YOUR-TWITTER-NAME https://stream.twitter.com/1/statuses/filter.json track='Justin Bieber'
```

Streamed output by small chunks à la `tail -f`:

```
# Send each new tweet (JSON object) mentioning "Apple" to another
# server as soon as it arrives from the Twitter streaming API:
$ http --stream -f -a YOUR-TWITTER-NAME https://stream.twitter.com/1/statuses/filter.json track=Apple \
| while read tweet; do echo "$tweet" | http POST example.org/tweets ; done
```

## 23 Sessions

By default, every request HTTPie makes is completely independent of any previous ones to the same host.

However, HTTPie also supports persistent sessions via the `--session=SESSION_NAME_OR_PATH` option. In a session, custom [HTTP headers](#) (except for the ones starting with `Content-` or `If-`), [authentication](#), and [cookies](#) (manually specified or sent by the server) persist between requests to the same host.

```
# Create a new session:
$ http --session=./session.json httpbin.org/headers API-Token:123
```

```
# Inspect / edit the generated session file:
$ cat session.json
```

```
# Re-use the existing session - the API-Token header will be set:
$ http --session=./session.json httpbin.org/headers
```

All session data, including credentials, cookie data, and custom headers are stored in plain text. That means session files can also be created and edited manually in a text editor—they are regular JSON. It also means that they can be read by anyone who has access to the session file.

### 23.1 Named sessions

You can create one or more named session per host. For example, this is how you can create a new session named `user1` for `httpbin.org`:

```
$ http --session=user1 -a user1:password httpbin.org/get X-Foo:Bar
```

From now on, you can refer to the session by its name (`user1`). When you choose to use the session again, any previously specified authentication or HTTP headers will automatically be set:



```
$ http --session=user1 httpbin.org/get
```

To create or reuse a different session, simply specify a different name:

```
$ http --session=user2 -a user2:password httpbin.org/get X-Bar:Foo
```

Named sessions's data is stored in JSON files in the `sessions` subdirectory of the `config` directory:

`~/.httpie/sessions/<host>/<name>.json`

(`%APPDATA%\httpie\sessions\<host>\<name>.json` on Windows).

If you have executed the above commands on a unix machine, you should be able list the generated sessions files using:

```
$ ls -l ~/.httpie/sessions/httpbin.org
```

## 23.2 Anonymous sessions

Instead of a name, you can also directly specify a path to a session file. This allows for sessions to be re-used across multiple hosts:

```
# Create a session:  
$ http --session=/tmp/session.json example.org
```

```
# Use the session to make a request to another host:  
$ http --session=/tmp/session.json admin.example.org
```

```
# You can also refer to a previously created named session:  
$ http --session=~/.httpie/sessions/another.example.org/test.json example.org
```

When creating anonymous sessions, please remember to always include at least one `/`, even if the session files is located in the current directory (i.e., `--session=./session.json` instead of just `--session=session.json`), otherwise HTTPie assumes a named session instead.

## 23.3 Readonly session

To use an existing session file without updating it from the request/response exchange after it has been created, specify the session name via `--session-read-only=SESSION_NAME_OR_PATH` instead.

```
# If the session file doesn't exist, then it is created:  
$ http --session-read-only=./ro-session.json httpbin.org/headers Custom-Header:orig-value
```

```
# But it is not updated:  
$ http --session-read-only=./ro-session.json httpbin.org/headers Custom-Header:new-value
```

## 24 Config

HTTPie uses a simple `config.json` file. The file doesn't exist by default but you can create it manually.

### 24.1 Config file directory

The default location of the configuration file is `~/.httpie/config.json` (or `%APPDATA%\httpie\config.json` on Windows).

The config directory can be changed by setting the `$HTTPIE_CONFIG_DIR` environment variable:

```
$ export HTTPIE_CONFIG_DIR=/tmp/httpie
$ http httpbin.org/get
```

To view the exact location run `http --debug`.

## 24.2 Configurable options

Currently HTTPie offers a single configurable option:

### 24.2.1 `default_options`

An `Array` (by default empty) of default options that should be applied to every invocation of HTTPie.

For instance, you can use this config option to change your default color theme:

```
$ cat ~/.httpie/config.json
```

```
{
  "default_options": [
    "--style=fruity"
  ]
}
```

Even though it is technically possible to include there any of HTTPie's options, it is not recommended to modify the default behaviour in a way that would break your compatibility with the wider world as that can generate a lot of confusion.

## 24.3 Un-setting previously specified options

Default options from the config file, or specified any other way, can be unset for a particular invocation via `--no-OPTION` arguments passed on the command line (e.g., `--no-style` or `--no-session`).

## 25 Scripting

When using HTTPie from shell scripts, it can be handy to set the `--check-status` flag. It instructs HTTPie to exit with an error if the HTTP status is one of 3xx, 4xx, or 5xx. The exit status will be 3 (unless `--follow` is set), 4, or 5, respectively.

```
#!/bin/bash

if http --check-status --ignore-stdin --timeout=2.5 HEAD httpbin.org/get &> /dev/null; then
    echo 'OK!'
else
    case $? in
        2) echo 'Request timed out!' ;;
        3) echo 'Unexpected HTTP 3xx Redirection!' ;;
        4) echo 'HTTP 4xx Client Error!' ;;
        5) echo 'HTTP 5xx Server Error!' ;;
        6) echo 'Exceeded --max-redirects=<n> redirects!' ;;
        *) echo 'Other Error!' ;;
    esac
fi
```

## 25.1 Best practices

The default behaviour of automatically reading `stdin` is typically not desirable during non-interactive invocations. You most likely want to use the `--ignore-stdin` option to disable it.

It is a common gotcha that without this option HTTPie seemingly hangs. What happens is that when HTTPie is invoked for example from a cron job, `stdin` is not connected to a terminal. Therefore, rules for [redirected input](#) apply, i.e., HTTPie starts to read it expecting that the request body will be passed through. And since there's no data nor `EOF`, it will be stuck. So unless you're piping some data to HTTPie, this flag should be used in scripts.

Also, it might be good to set a connection `--timeout` limit to prevent your program from hanging if the server never responds.

## 26 Meta

### 26.1 Interface design

The syntax of the command arguments closely corresponds to the actual HTTP requests sent over the wire. It has the advantage that it's easy to remember and read. It is often possible to translate an HTTP request to an HTTPie argument list just by inlining the request elements. For example, compare this HTTP request:

```
POST /post HTTP/1.1
Host: httpbin.org
X-API-Key: 123
User-Agent: Bacon/1.0
Content-Type: application/x-www-form-urlencoded

name=value&name2=value2
```

with the HTTPie command that sends it:

```
$ http -f POST httpbin.org/post \
  X-API-Key:123 \
  User-Agent:Bacon/1.0 \
  name=value \
  name2=value2
```

Notice that both the order of elements and the syntax is very similar, and that only a small portion of the command is used to control HTTPie and doesn't directly correspond to any part of the request (here it's only `-f` asking HTTPie to send a form request).

The two modes, `--pretty=all` (default for terminal) and `--pretty=none` (default for redirected output), allow for both user-friendly interactive use and usage from scripts, where HTTPie serves as a generic HTTP client.

As HTTPie is still under heavy development, the existing command line syntax and some of the `--OPTIONS` may change slightly before HTTPie reaches its final version 1.0. All changes are recorded in the [change log](#).

### 26.2 User support

Please use the following support channels:

- [GitHub issues](#) for bug reports and feature requests.
- [Our Gitter chat room](#) to ask questions, discuss features, and for general discussion.

- [StackOverflow](#) to ask questions (please make sure to use the [httpie](#) tag).
- Tweet directly to [@clihttp](#).
- You can also tweet directly to [@jakubroztocil](#).

## 26.3 Related projects

### 26.3.1 Dependencies

Under the hood, HTTPie uses these two amazing libraries:

- [Requests](#) — Python HTTP library for humans
- [Pygments](#) — Python syntax highlighter

### 26.3.2 HTTPie friends

HTTPie plays exceptionally well with the following tools:

- [jq](#) — CLI JSON processor that works great in conjunction with HTTPie
- [http-prompt](#) — interactive shell for HTTPie featuring autocomplete and command syntax highlighting

### 26.3.3 Alternatives

- [httpcat](#) — a lower-level sister utility of HTTPie for constructing raw HTTP requests on the command line.
- [curl](#) — a "Swiss knife" command line tool and an exceptional library for transferring data with URLs.

## 26.4 Contributing

See [CONTRIBUTING.rst](#).

## 26.5 Change log

See [CHANGELOG](#).

## 26.6 Artwork

- Logo by [Cláudia Delgado](#).
- Animation by [Allen Smith](#) of GitHub.

## 26.7 Licence

BSD-3-Clause: [LICENSE](#).

## 26.8 Authors

[Jakub Roztocil](#) ([@jakubroztocil](#)) created HTTPie and [these fine people](#) have contributed.